


Needle Roller Bearings

With Seals

-Without Inner Ring



RNA 49..RS

RNA 49..RS

Shaft dia. mm	Series		Dimensions mm				Basic load ratings		Limited speed
	RNA 49...RS	RNA 49...2RS	dr	D	B	r min	Dynamic C kgf	Static Co kgf	Oil rpm(1)
14	RNA 4900 RS	RNA 4900 2RS	14	22	13	0.3	870	930	14000
16	RNA 4901 RS	RNA 4901 2RS	16	24	13	0.3	910	1020	13000
20	RNA 4902 RS	RNA 4902 2RS	20	28	13	0.3	1030	1270	10000
22	RNA 4903 RS	RNA 4903 2RS	22	30	13	0.3	1100	1440	9000
25	RNA 4904 RS	RNA 4904 2RS	25	37	17	0.3	1920	2230	8000
30	RNA 4905 RS	RNA 4905 2RS	30	42	17	0.3	2090	2610	6500
35	RNA 4906 RS	RNA 4906 2RS	35	47	17	0.3	2250	2990	5500
42	RNA 4907 RS	RNA 4907 2RS	42	55	20	0.6	2800	4260	4800
48	RNA 4908 RS	RNA 4908 2RS	48	62	22	0.6	3720	5900	4200
52	RNA 4909 RS	RNA 4909 2RS	52	68	22	0.6	3740	6180	3800
58	RNA 4910 RS	RNA 4910 2RS	58	72	22	0.6	4070	6980	3400

Oil lubrication can be applied to increase the speed limit.